

Degreaser Spray

Multipurpose, High KB Index cleaning solvent

APPLICATIONS

Degreaser for general maintenance, for all mechanical organs, plastics...

Cleans residues of lubricants, greases, inks, adhesives, resins...

Prepares surfaces before gluing or painting operations.

Can be used on powered-off electrical equipment.

Shake the aerosol before use – Spray from a 10-15 cm distance.

Keep away from heat, sparks, and flames. Do not expose to heat and temperatures exceeding 50°C. Even when empty, do not puncture or incinerate the container.

ADVANTAGES

Quick evaporation

High solvency

Non-flammable propellant gas: CO₂

Can be used upside-down for an easier manipulation of the spray

Compatible with most plastics, elastomers, and metals

TYPICAL CHARACTERISTICS

Properties	Units	Standards	Degreaser Spray
Color	-	Visual	Colorless
Density at 15°C	kg/m ³	ISO 12185	750
Viscosity at 40°C	mm ² /s	ISO 3104	0.8
KB index	-	ASTM D 1133	90
Flash point (closed-cup)	°C	ISO 2719	24
Copper strip test	-	ISO 2160	1a
Dielectric breakdown voltage	V	IEC 156	50 000

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial advisor or downloaded at ms-sds.totalenergies.com