



# Martol EV 10 AQ

## DESCRIPTION

Whether you need to cut, drill, grind, or form metal parts, TotalEnergies Lubrificants has the right metalworking fluid for you. Our products are designed to meet the highest standards of quality and performance, and to help you optimize your operations.

**Martol** is a versatile range of high-performance forming fluids, shaping a path of consistency for you and your operations.

## APPLICATIONS

Martol EV products are formulated with lightweight hydrocarbon cuts and high-performance additives, reducing, or eliminating the need for degreasing.

**Martol EV 10 AQ** is an evaporating oil for low and medium severity drawing on steel and non-ferrous metals. It's designed for the stamping of aluminum <2mm thick.

## RECOMMENDATIONS

**Martol EV 10 AQ** allows a reduction of VOC compared to other evanescent forming lubricants.

- Degreasing possible at room temperature
- High flash point, reducing fire-risks
- Excellent wetting properties
- Applicability by brush, spraying or roller
- Non staining of non-ferrous materials

## TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL EV 10 AQ
Color	Visual	-	Clear
Viscosity at 20°C	NFT 60-100	mm <sup>2</sup> /s	3.8
Viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	2.5
Flash point	EN 22719	°C	> 104

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at [ms-sds.totalenergies.com](https://ms-sds.totalenergies.com)